



BUSSOLE DI INIEZIONE PER CAMERA CALDA MANIFOLD INLET BUSHINGS

<i>SERIE</i>	<i>M</i>	$\varnothing D$	$\varnothing D1$	$\varnothing D2$	<i>L</i>	<i>L1</i>	<i>L2</i>	<i>CH</i>
BIS / BIR	22x1.5	24	4	6	40	7	29.9	21
BIS / BIR	22x1.5	24	6	8	50	7	39.9	21
BIS / BIR	28x1.5	38	8	10	64	10	53.9	27
BIS / BIR	36x1.5	50	10	16	68	12	55.8	46
BIS	Bussola Iniezione Standard Standard Manifold Bushing <i>(Si consiglia utilizzo con resistenza / Suggested with heater + TC included)</i>							
BIR	Bussola Iniezione con inserto conduttivo Manifold Bushing with thermal conductive insert <i>(solo per materiali di uso comune ex. : PP / HDPE / LDPE / PS)</i> <i>(only for commodity materials i.e.: PP / HDPE / LDPE / PS)</i> <i>(Da impiegarsi senza resistenza / To be used without heater)</i>							
Material <i>Material</i>	ACCIAIO BONIFICATO Pre-Hardn. Steel							
Come procedere all'ordinazione / How to order								
Ex. = Serie + M + d1 + L = BIS22440								